



Connexion SQUALE 6 kit for sealed connection up to 4 conductors of wire section 6 mm²

Quick, waterproof, efficient



Characteristics

Capacity 1 conductor (mm²): **1.5-50**
Capacity 2 conductors (mm²): **1.5-10**
Capacity 3 conductors (mm²): **1.5-10**
Capacity 4 conductors (mm²): **1.5-6**
Dimensions (mm): **105 x 55**

Norms

- EN 50393
- IP X8

Benefits

- IPX8 for immersed installations.
- Full range dedicated to residential and tertiary.
- Non toxic.

Compliance marks



GENERAL INFORMATION

Technical details

Voltage: 0.6 to 1 kV.

Application(s)

For connecting, insulating, sealing and protecting copper electrical cables.
Supplied with cable centring device and cable ties for holding conduits.

Instructions

1. Strip and connect the cables.
2. Insert the separator and centre the cables in the enclosure.
3. Close the enclosure and lock in the conduits.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 11
 Length (cm) : 12
 Depth (cm) : 7
 Net weight (kg) : 0,14
 Gross weight (kg) : 0,14



Outer package 1



x 100

Carton box

Height (cm) : 44
 Length (cm) : 50
 Depth (cm) : 38
 Net weight (kg) : 14
 Gross weight (kg) : 14,56



Outer package 2



x 800

Pallet

Height (cm) : 105
 Length (cm) : 80
 Depth (cm) : 120
 Net weight (kg) : 116,48
 Gross weight (kg) : 147

