

Suspension kit wire rope \varnothing 1.5 x 150 m and 100 locks



Characteristics

Cable \varnothing (mm): **1.5**
 Cable length (m): **150**
 Load accepted (kg): **35**
 Use: **Interior**



GENERAL INFORMATION

Description

Contains:

- 100 BIZ 710 406 suspension locks.
- 1 cable reel \varnothing 1.5 mm x 150 m BIZ 710 351.

Technical details

Lock housing: ZA2 zinc.
 Locking wedge: hardened steel, minimum Rockwell 56C.
 Lock spring: type 302 stainless steel.
 Latch cover: UV-stabilised PP.
 Lock button: PP reinforced with 33% fibreglass.
 Cable: braided steel.
 Cable core: 7 x 7 steel strands.

Advices

Observe the maximum and minimum usage loads.
 Check that the cable has no traces of oil, paint or rust.
 Use only for suspension of equipment under static load.
 Do not use outside or in a chlorinated, marine or corrosive environment.
 Do not use for hoisting.
 Do not use to splice two cables.
 Do not use for suspension of more than 60° from the vertical axis.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 23,5
 Length (cm) : 26,3
 Depth (cm) : 7
 Net weight (kg) : 3,93
 Gross weight (kg) : 4,08



Outer package 1



x 4.00

Carton box

Height (cm) : 28,4
 Length (cm) : 27,4
 Depth (cm) : 25,9
 Net weight (kg) : 16,32
 Gross weight (kg) : 16,9



Outer package 2



x 64.00

Pallet

Height (cm) : 85
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 280
 Gross weight (kg) : 298

