

# Wire pulling lubricant BIZ'LUB



## Benefits

- Non-flammable, non-corrosive, non-toxic.
- For use with high and low-current cables.
- High lubricating capability.

## GENERAL INFORMATION

### Technical details

Ph neutral (6.5 ± 0.5).  
 Operating temperature: -5 °C to +82 °C (freezes at -5 °C).  
 Storage temperature: +4 °C to +40 °C.  
 Density: 1.010 ± 0.01 g/ml.  
 Viscosity: 3400 ± 200 cps.  
 Dry residue: 12 °C.  
 Volume: 1 l.

### Life span

5 years.

### Application(s)

To ease passage of cables and wires through electrical conduits, ducts and pipes.

### Instructions

1. Leave to dry before switching on power.

## LOGISTIC INFORMATION

### Packaging



#### Plastic bottle

Height (cm) : 29  
 Length (cm) : 8  
 Depth (cm) : 8  
 Net weight (kg) : 1,03  
 Gross weight (kg) : 1,08



### Outer package 1



#### Carton box

Height (cm) : 31  
 Length (cm) : 34,5  
 Depth (cm) : 26,5  
 Net weight (kg) : 12,36  
 Gross weight (kg) : 13,41



x 12.00

### Outer package 2



#### Pallet

Height (cm) : 110  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 333,72  
 Gross weight (kg) : 377,07



x 324.00