

Screw connector 40A 500V 3 x 6mm² brass insert (x50)

Benefits

- Suitable for earth connection.
- Brass coated that gives a better conductivity.
- Clear plastic material for a better connections control.

Norms

- ☑ IEC 60998-2-1: 2002
- ☑ IEC 60998-1: 2002

GENERAL INFORMATION

Description

Screw Connectors 40A.
For flexible and rigid cable up to 3 x 6 mm².

Technical details

Voltage (V) : 500.
Amperage (A) : 40.
Connection material : brass.
Plastic material : polycarbonate.
Glow wire test (°C) : 850.
Zinc plated steel screw M5 : Square + Philips (PH).
Application temperature (°C): -35°C to 120.

Application(s)

For flexible and rigid cable up to 3 x 6 mm². or 4 x 2.5 mm².

LOGISTIC INFORMATION

Packaging



Bucket

Height (cm) : 13,5
 Length (cm) : 8
 Depth (cm) : 8
 Net weight (kg) : 0,22
 Gross weight (kg) : 0,26



Outer package 1



Carton box

Height (cm) : 14
 Length (cm) : 42
 Depth (cm) : 42
 Net weight (kg) : 5,5
 Gross weight (kg) : 7,5



x 25.00

Outer package 2



Pallet

Height (cm) : 115
 Length (cm) : 126
 Depth (cm) : 84
 Net weight (kg) : 264
 Gross weight (kg) : 375



x 1200.00